

USING CASE-BASED REASONING FOR DATABASE QUERY OPTIMIZATION IN UBIQUITOUS ENVIRONMENTS

Lourdes MARTÍNEZ-MEDINA and Christophe BOBINEAU

Firstname.Lastname@imag.fr

UDLA-P / CENTIA, LAFMIA (UMI 3175)

Laboratoire d'Informatique de Grenoble LIG – HADAS

Ubiquitous computing environment

2

Environment characteristics

- Physically constrained
- Autonomous
- Dynamic
- Heterogeneous

Query evaluation

Any information at any time from any place using any device

- Lack of metadata

device

Query optimization




Content

3

- ✓ Ubiquitous computing environments
- Classical query optimization techniques and ubiquitous environments
- Query optimization using case-based reasoning
- Conclusions and future works

Classical query evaluation

4



Optimization process

5

- Search space exploration
 - ▣ Using algebraic transformation
 - ▣ Using heuristics
 - ▣ Random exploration
- Execution cost estimation
 - ▣ For each generated plan
 - ▣ Using cost function or rules
- Extensive use of metadata and statistics that are not always available


Content

6

- ✓ Ubiquitous computing environments
- ✓ Classical query optimization techniques and ubiquitous environments
- Query optimization using case-based reasoning
 - Data model
 - Pseudo-random query plan generation
 - Case-based reasoning adaptation to query optimization
- Conclusions and future work

Query optimization using case-based reasoning

7



- The cost of execution plans cannot be evaluated *a priori*, so **lets try and see!**
- (Pseudo-)random search space exploration where just ONE execution plan is generated
- Measures during query plan execution
- Reuse learned plans
- Continuous learning

Advantages

8

😊 No need of statistics

- Optimization where classical techniques are not applicable
- Progressive optimization
 - Can be accelerated by preloading/sharing of case bases

😊 Personalization of optimization objectives

- Cost function depending on measures

New Problem

R1 : Restaurant(nom, adresse, ville)
R2 : Ville (nomVille, NumDept)
R3 : Region(NumDept, NomRegion)

9

□ Q

Select Restaurant.nom, Restaurant.adresse, Restaurant.ville
From Restaurant, Ville, Region
Where Region.nom = 'Rhone Alpes' and Restaurant.specialite = 'Italienne' and
Restaurant.ville = Ville.nom and Ville.numDept = Region.numDept

Problem

Q

Select = {R1.a1, R1. a2, R1. a3}
From = {R1, R2, R3}
Where = {Sel(R3.nom='Rhone Alpes'), Sel(R1.specialite='Italienne'),
Join(R1.ville = R2.nom), Join(R2.numDept = R3.numDept)}

Context



Free memory = 400 KB
CPU charge = 75%
Available Energy = 70%

Optimization objective

$F(\text{memory})$

Pseudo-random query plan generation

10



Query 1


Select Resto.nom, Resto.adresse, Resto.ville

From Resto, Ville, Region

Where Region.nom = 'RA' and Resto.spec = 'It' and
Resto.ville = Ville.nom and
Ville.numDept = Region.numDept

Case-based reasoning process adaptation to query optimization

11




Query classification and similarity

12

- Similarity guided by adaptation possibilities
- Query classification
 - ▣ Queries that can be solved by the same set of query plan shapes
 - ▣ Common features
 - Same data sources
 - Same join conditions
 - Same selection operators (but not values)
- Query similarity
 - ▣ Queries in the same query class are similar
 - ▣ Similarity is the base for retrieval process
 - Identify query class
 - Explore equivalent cases
 - ▣ Similarity guide storage of cases

Retrieve similar queries

13



□ Q₁

Select	= {R1.nom, R1. adres, R1. specialite}
From	= {R1, R2, R3}
Where	= {Sel(R3.nom='Rhone Alpes'), Sel(R1.specialite='Italienne'), Join(R1.ville = R2.nom), Join(R2.numDept = R3.numDept)}

□ Q₂

Select	= {R1.nom, R1. adres}
From	= {R1, R2, R3}
Where	= {Sel(R3.nom='Alsace'), Sel(R1.specialite='Indienne'), Join(R1.ville = R2.nom), Join(R2.numDept = R3.numDept)}

Case

R1 : Restaurant(nom, adresse, ville)
 R2 : Ville (nomVille, NumDept)
 R3 : Region(NumDept, NomRegion)

14

□ Q₁


Select Restaurant.nom, Restaurant.adresse
 From Restaurant, Ville, Region
 Where Region.nom = 'Alsace' and Restaurant.specialite = 'Indienne' and
 Restaurant.ville = Ville.nom and Ville.numDept = Region.numDept

Case 3

Q

Select = {R1.a1, R1. a2, R1. a3}
 From = {R1, R2, R3}
 Where = {Sel(R3.nom='Rhone Alpes'), Sel(R1.specialite='Italienne'),
 Join(R1.ville = R2.nom), Join(R2.numDept = R3.numDept)}

Query plan



Evaluation

Consumed resources

Memory = 420 KB

CPU = 5%


Energy = 8%

Performance

Execution time = 150 ms

Adaptation process

15



□ Adaptation concerns

- Projection attributes
- Selection condition (fix values for selection)

□ The adaptation process depends on the similarity level between the queries

Similarity level	Equivalent clauses	Different clauses
4	selectClause, fromClause and whereClause	---
3	fromClause and whereClause	selectClause
2	selectClause and fromClause	whereClause
1	fromClause	selectClause and whereClause
0	---	fromClause, selectClause and whereClause

Content

16

- ✓ Ubiquitous computing environments
- ✓ Classical query optimization techniques and ubiquitous environments
- ✓ Query optimization using case-based reasoning
- Conclusions and future work



Conclusions

17

- We proposed a query optimization technique that
 - ▣ Allows the query optimization when no metadata is available
 - ▣ Exploits case-based reasoning
 - ▣ Allows the personalization of optimization objectives
- The contribution of our work is
 - ▣ Case-based reasoning adaptation to query optimization
 - ▣ Data model for the knowledge representation
 - ▣ First prototype implementation

First results

- Evaluation time



Future work

19

- Extensive experimental evaluation
- Improvement of knowledge acquisition and exploitation
 - ▣ Sub-queries
 - ▣ Knowledge preloading/sharing
- Dynamicity management
 - ▣ React to changes in the environment
 - ▣ Knowledge maintenance
- Other application domains

Thank you

20



Bibliography

- [1] Features of similarity and category-based induction, 1997
- [2] A. Aamodt and E. Plaza. Case-based reasoning: Foundational issues, methodological variations, and system approaches. *AI Communications*, 7(1):39{59, 1994
- [3] E. Bardram. Activity-based computing: support for mobility and collaboration in ubiquitous computing. *Personal Ubiquitous Comput.*, 9(5):312{322, 2005
- [4] G. A. A. Deyand, P. Brown, and et al. Towards a better understanding of context and context-awareness. In: *Proceedings of the 1st international symposium on Handheld and Ubiquitous Computing (HUC 1999)*, September 1999
- [5] M. Franklin. Challenges in ubiquitous data management. In R. Wilhelm, editor, *Informatics - 10 Years Back. 10 Years Ahead.*, pages 24{33. Springer-Verlag, 2001
- [6] Y. Ioannidis. Query optimization. *ACM Comput. Surv.*, 28(1):121{123, 1996
- [7] L. D. Mantaras, R. McSherry, and et al. Retrieval, reuse, revision and retention in case-based reasoning. *Knowl. Eng. Rev.*, 20(3):215{240, 2005

Bibliography

- [8] Microsoft. Execution plan caching and reuse. <http://technet.microsoft.com/enus/library/bb545450.aspx>, 2008
- [9] J. Nilsson. Introduction to Machine Learning (An Early Draft to a proposed textbook). 1996
- [10] M. Othman-Abdallah. Optimisation de requetes par apprentissage. PhD thesis, Institut National Polytechnique de Grenoble
- [11] F. Perich, S. Avancha, and et al. Prole driven data management for pervasive environments. In In: Proceedings of the 13th International Conference on Database and Expert Systems Applications (DEXA 2002), pages 361{370, London, UK, 2002. Springer-Verlag
- [12] M. Stillger, G. Lohman, V. Markl, and M. Kandil. Leo - db2's learning optimizer. In: Proceedings of the 27th International Conference on Very Large Data Bases (VLDB 2001), pages 19{28, San Francisco, CA, USA, 2001. Morgan Kaufmann Publishers Inc
- [13] D. Subramanian and K. Subramanian. Query optimization in multi-database systems. Distrib. Parallel Databases, 6(2):183{210, 1998
- [14] A. Tversky and I. Gati. Studies of similarity. 1978