Revisiting Numerical Pattern Mining with Formal Concept Analysis

Mehdi Kaytoue[1], Sergei O. Kuznetsov[2], and Amedeo Napoli[1]

[1] Laboratoire lorrain de recherche en informatique et ses applications (LORIA)
Campus Scientifique, B.P. 70239 – Vandœuvre-lès-Nancy – France

[2] Higher school of economics, State University (HSE)
Pokrovskiy Bd. 11 – 109028 Moscow – Russia

Résumé : In this paper, we investigate the problem of mining numerical data in the framework of Formal Concept Analysis. The usual way is to use a scaling procedure –transforming numerical attributes into binary ones– leading either to a loss of information or of efficiency, in particular w.r.t. the volume of extracted patterns. By contrast, we propose to directly work on numerical data in a more precise and efficient way, and we prove it. For that, the notions of closed patterns, generators and equivalent classes are revisited in the numerical context. Moreover, two original algorithms are proposed and used in an evaluation involving real-world data, showing the predominance of the present approach.

1 Introduction

In this paper, we investigate the problem of mining numerical data. This problem arises in many practical situations, e.g. analysis of gene and transcriptomic data in biology, soil characteristics and land occupation in agronomy, demographic data in economics, temperatures in climate analysis, etc. We introduce an original framework for mining numerical data based on advances in itemset mining and in Formal Concept Analysis (FCA, [1]), respectively condensed representations of itemsets and pattern structures in FCA [2]. The mining of frequent itemsets in binary data, considering a set of objects and a set of associated attributes or items, is studied for a long time and usually involves the so-called "pattern flooding" problem [3]. A way of dealing with pattern flooding is to search for equivalence classes of itemsets, i.e. itemsets shared by the same set of objects (or having the same image). For an equivalence class, there is one maximal itemset, which corresponds to a "closed set", and possibly several minimal elements corresponding to "generators" (or "key itemsets"). From these elements, families of association rules can be extracted [3]. These particular itemsets are also related to FCA , where a concept lattice is built from a binary context and where formal concepts are closed sets of objects and attributes.

The present work is rooted both in FCA and pattern mining with the objective of extracting interval patterns from numerical data. Our approach is based on "pattern

structures" where complex descriptions can be associated with objects. In [4], in the context of gene expression data mining, we introduced pattern structures for numerical data, and showed how to extract closed interval patterns : an interval pattern is a vector of intervals, each dimension corresponding to a range of values of a given attribute ; it is closed when composed of the smallest intervals characterizing a same set of objects.

We here complete and extend this first attempt. Considering numerical data, some general characteristics of equivalence classes remain, e.g. one maximal element which is a closed pattern and possibly several generators which are minimal patterns w.r.t. a subsumption relation defined on patterns. We show that directly extracting patterns from numerical is more efficient using pattern structures than working with binary data and associated scaling procedures. We also provide a semantic to interval patterns in the Euclidean space, and design and experiment algorithms to extract frequent closed interval patterns and their generators.

The problem of mining patterns in numerical data is usually referred as quantitative itemset/association rule mining [5]. Generally, an appropriate discretization splits attribute ranges into intervals maximizing some interest functions, e.g. support, confidence. However, none of these works discusses the notion of equivalence classes, closed patterns, and generators, and this is one of the originality of the present paper.

The plan of the paper is as follows. In the next section, we introduce the problem of mining numerical data and interval patterns. Then, we recall the basics of FCA and interordinal scaling. We pose a number of questions that we propose to answer using our framework of interval pattern structures. We then detail two original algorithms for extracting closed interval patterns and their generators that we experiment in the last section. Finally, we end the paper in discussing related work and giving perspectives to the present research work. Note also that an extended version of this paper can be found in [6, 7], along with algorithms pseudo-code and a deeper discussion on the usefulness of interval patterns in classification problems and privacy preserving data-mining.

2 Problem definition

We propose a definition of interval patterns for numerical data. Intuitively, each object of a numerical dataset corresponds to a vector of numbers, where each dimension stands for an attribute. Accordingly, an interval pattern is a vector of intervals, where each dimension describes the range of possible values for a given numerical attribute associated with some objects. We only consider finite intervals and that the set of attributes/dimensions is ordered.

Numerical dataset, interval pattern and support. A numerical dataset is given by a set of objects G, a set of numerical attributes M, where attribute $m \in M$ has for range a set of real numbers W_m. $m(g) = w$ means that w is the value of attribute m for object g. An interval pattern is a vector of intervals $d = \langle [a_i, b_i] \rangle_{i \in \{1,...,|M|\}}$ where $a_i, b_i \in W_{m_i}$, and each component corresponds to an attribute following a canonical order on vector dimensions, and $|M|$ denotes the number of attributes. An object g is in the image of an interval pattern $\langle [a_i, b_i] \rangle_{i \in \{1,...,|M|\}}$ when $m_i(g) \in [a_i, b_i]$, $\forall i \in \{1, ..., |M|\}$. The support of d, denoted by $sup(d)$, is the cardinality of the image of d.

	$m_1 \leq 4$	$m_1 \leq 5$	$m_1 \leq 6$	$m_1 \geq 4$	$m_1 \geq 5$	$m_1 \geq 6$	$m_2 \leq 7$	$m_2 \leq 8$	$m_2 \leq 9$	$m_2 \geq 7$	$m_2 \geq 8$	$m_2 \geq 9$	$m_3 \leq 4$	$m_3 \leq 5$	$m_3 \leq 6$	$m_3 \leq 8$	$m_3 \geq 4$	$m_3 \geq 5$	$m_3 \geq 6$	$m_3 \geq 8$
g_1		×	×	×	×		×	×	×	×					×	×	×	×	×	
g_2			×	×	×	×		×	×	×	×		×	×	×	×	×			
g_3	×	×	×	×				×	×	×	×			×	×	×	×	×		
g_4	×	×	×	×					×	×	×	×				×	×	×	×	×
g_5		×	×	×	×			×	×	×	×			×	×	×	×	×		

TABLE 2 – Interordinally scaled context encoding the numerical dataset from Table 1.

Running example. Table 1 is a numerical dataset with objects in $G = \{g_1, ..., g_5\}$, attributes in $M = \{m_1, m_2, m_3\}$. The range of m_1 is $W_{m_1} = \{4, 5, 6\}$, and we have $m_1(g_1) = 5$. Here, we do not consider either missing values or multiple values for an attribute. $\langle [5, 6], [7, 8], [4, 6] \rangle$ is an interval pattern in Table 1, where a vector dimension i corresponds to an attribute $m_i \in M$, with image $\{g_1, g_2, g_5\}$ and support 3. The fact that $a_i, b_i \in W_{m_i}$ in the definition of an interval pattern makes the search space finite.

	m_1	m_2	m_3
g_1	5	7	6
g_2	6	8	4
g_3	4	8	5
g_4	4	9	8
g_5	5	8	5

TABLE 1 – A numerical dataset.

Interval pattern search space. Given a set of attributes $M = \{m_i\}_{i \in \{1, |M|\}}$, the search space of interval patterns is the set D of all interval vectors $\langle [a_i, b_i] \rangle_{i \in \{1, ..., |M|\}}$, with $a_i, b_i \in W_{m_i}$. The size of the search space is given by

$$|D| = \prod_{i \in \{1, ..., |M|\}} (|W_{m_i}| \times (|W_{m_i}| + 1))/2$$

In our example, all possible intervals for m_1 are in $\{[4, 4], [5, 5], [6, 6], [4, 5], [5, 6], [4, 6]\}$. Considering also attributes m_2 and m_3, we have $6 \times 6 \times 10 = 360$ patterns.

The classical problem of "pattern flooding" in data-mining is even worst for numerical data. Indeed, with three attributes, there is only $2^3 = 8$ possible itemsets, compared to the 360 interval patterns in the example with same amount of attributes. A solution widely investigated in itemset-mining relies on condensed representations with so called closed itemsets and generators, e.g. in [3]. Moreover, the analysis of numerical datasets can be considered within the formal concept analysis framework (FCA) [1], which is closely related to itemset-mining [8]. Accordingly, we are interested in adapting the notions of (frequent) closed itemsets and their generators to interval patterns within the FCA framework, and in providing them with appropriate semantics.

3 Interval patterns in FCA

In their seminal book on FCA, [1] define a discretization procedure turning numerical data into binary data called *interordinal scaling*. It allows to encode in binary data any interval of values from a numerical dataset.

Formal concept analysis. FCA starts with a formal context (G, N, I) where G denotes a set of objects, N a set of attributes, or items, and $I \subseteq G \times N$ a binary relation between G and N. The statement $(g, n) \in I$, or gIn, means : "the object g has attribute n". The

two operators $(\cdot)'$ define a Galois connection between the powersets $(\mathfrak{P}(G), \subseteq)$ and $(\mathfrak{P}(N), \subseteq)$, with $A \subseteq G$ and $B \subseteq N : A' = \{n \in N \mid \forall g \in A : gIn\}$ and $B' = \{g \in G \mid \forall n \in B : gIn\}$. A pair (A, B), such that $A' = B$ and $B' = A$, is called a *(formal) concept*, while A is called the $extent$ and B the $intent$.

From an itemset-mining point of view, concept intents correspond to closed itemsets, since $(.)''$ is a closure operator. For any subset $B \subseteq N$, B'' is the largest itemset having the same image. An equivalence class is a set of itemsets with same closure (and same image). A subset $B \subseteq N$ is a generator iff $\nexists C \subset B$ with $C' = B'$. Generators are the smallest elements w.r.t. set inclusion in an equivalence class.

Interordinal scaling. Given a numerical attribute m with range W_m, interordinal scaling builds a binary table with $2 \times |W_m|$ binary attributes. They are denoted by "$m \leq w$" and "$m \geq w$", $\forall w \in W_m$, and called IS-items. An object g has an IS-item "$m \leq w$" (resp. "$m \geq w$") iff $m(g) \leq w$ (resp. $m(g) \geq w$). Applying this scaling to our example gives Table 2. It is possible to apply classical mining algorithms to process this table for extracting itemsets composed of IS-items. These itemsets are called IS-itemsets in the following.

IS-itemsets can be turned into interval patterns, since an IS-item gives a constraint for an attribute m on its range W_m. For example, the IS-itemset $\{m_1 \leq 5, m_1 \leq 6, m_1 \geq 4, m_2 \leq 9, m_2 \geq 7\}$ corresponds to the interval pattern $\langle [4, 5], [7, 9], [4, 8] \rangle$. We have here the interval $[4, 8]$ for attribute m_3, i.e. covering its whole range, since no constraint in the itemset involves m_3. Therefore, mining interval patterns can be considered after discretizing numerical data. However, this scaling builds binary data with a very important amount of binary attributes compared to the original ones, even with our small example. Hence, when original data are very large, the size of the resulting formal context involves hard computations. Accordingly, this raises the following questions : (i) Can we avoid scaling and directly work on numerical data instead of searching for IS-itemsets ? (ii) Can we adapt the notions of condensed representations such as closed patterns and generators for numerical data, and efficiently compute those patterns ? (iii) What would be the semantics that could be provided to closed patterns and generators ?

4 Revisiting numerical pattern mining

In this section, we answer those questions. First, we show that a closure operator can be defined for interval patterns based upon their image. Then, we provide interval patterns with appropriate semantics for defining the notion of equivalence classes of patterns, closed and generator patterns. After discussing why working with interordinal scaling is not acceptable thanks to the semantics of interval patterns, we propose two efficient algorithms for mining closed interval patterns and generators.

4.1 A closure operator for interval patterns

We use the formalism of pattern structures [2], an extension of formal contexts to complex data in FCA. It defines a closure operator from any partially ordered set of object descriptions called patterns.

Formally, let G be a set of objects, $(D, \sqcap)$ be a semi-lattice of object descriptions, and $\delta : G \rightarrow D$ be a mapping : $(G, (D, \sqcap), \delta)$ is called a *pattern structure*. Elements of D are called *patterns*, and ordered as follows $c \sqcap d = c \iff c \sqsubseteq d$. Intuitively, objects in G have descriptions in $(D, \sqcap)$. For example, g_1 in Table 1 has description $\langle [5,5], [7,7], [6,6] \rangle$ where D is the set of all possible interval patterns ordered with $\sqcap$ which is made precise below. Let the two operators $(.)^{\square}$ defined as follows, with $A \subseteq G$ and $d \in (D, \sqcap)$

$$d^{\square} = \{g \in G | d \sqsubseteq \delta(g)\} \qquad A^{\square} = \bigsqcap_{g \in A} \delta(g)$$

These operators form a Galois connection between $(\mathfrak{P}(G), \subseteq)$ and $(D, \sqsubseteq)$. $(.)^{\square\square}$ is a closure operator, meaning that any pattern d such as $d = d^{\square\square}$ is closed.

Interval pattern structures. Interval patterns can be ordered within a meet-semi-lattice when the infimum is defined as follows [4]. Let $c = \langle [a_i, b_i] \rangle_{i \in \{1,...,|M|\}}$, and $d = \langle [e_i, f_i] \rangle_{i \in \{1,...,|M|\}}$ two intervals patterns. Infimum is given by $c \sqcap d = \langle [min(a_i, e_i), max(b_i, f_i)] \rangle_{i \in \{1,...,|M|\}}$. The ordering relation induced by this definition is : $c \sqsubseteq d \iff [e_i, f_i] \subseteq [a_i, b_i], \ \forall i \in \{1, ..., |M|\}$.

Consider now a numerical dataset, e.g. Table 1. $(D, \sqsubseteq)$ is the finite ordered set of all interval patterns. $\delta(g) \in D$ is the pattern associated to an object $g \in G$. Then :

$$\langle [5,6], [7,8], [4,8] \rangle^{\square} = \{g_1, g_2, g_5\}$$
$$\{g_1, g_2, g_5\}^{\square} = \langle [5,6], [7,8], [4,6] \rangle$$

Hence $\langle [5,6], [7,8], [4,8] \rangle$ is closed, its closure being $\langle [5,6], [7,8], [4,6] \rangle$.

4.2 Semantics

An interval pattern d is a $|M|$-dimensional vector of intervals and can be represented by a hyper-rectangle (or rectangle for short) in Euclidean space $\mathbb{R}^{|M|}$, whose sides are parallel to the coordinate axes. This geometrical representation provides a semantics for interval patterns. In formal terms, this interpretation is given by $\mathcal{I} = (\mathbb{R}^{|M|}, (.)^{\mathcal{I}})$ where $\mathbb{R}^{|M|}$ is the interpretation domain, and $(.)^{\mathcal{I}} : D \rightarrow \mathbb{R}^{|M|}$ the interpretation function. Figure 1 gives four interval pattern representations in $\mathbb{R}^2$, with only attributes m_1 and m_3 of our example. The image of d_1 is given by all objects g whose description $\delta(g)$ is included in the rectangle associated with d_1, i.e. the set $\{g_1, g_3, g_4, g_5\}$. We can interpret the closure operator $(.)^{\square\square}$ according to this semantics. The first operator $(.)^{\square}$ applies to a rectangle and returns the set of objects whose description is included in this rectangle. The second operator $(.)^{\square}$ applies to a set of objects and returns the smallest rectangle that contains their descriptions, i.e. the convex hull of their corresponding descriptions.

4.3 Closed interval patterns and generators

Now, we can revisit the notion of equivalence classes of itemsets [3] : an equivalence class of interval patterns is a set of rectangles containing the same object descriptions (based on all rectangles in the searchspace given in Section 2). This enables to define the notions of (frequent) closed interval patterns ((F)CIP) and (frequent) interval pattern generators ((F)IPG), adapted from classical case.



$d_1 = \langle [4,5],[5,8] \rangle$
$d_1^{\square} = \{g_1, g_3, g_4, g_5\}$
$d_2 = \langle [4,5],[4,5] \rangle$
$d_2^{\square} = \{g_3, g_5\}$
$d_3 = \langle [5,6],[4,4] \rangle$
$d_3^{\square} = \{g_2\}$
$d_4 = \langle [6,6],[4,8] \rangle$
$d_4^{\square} = \{g_2\}$

FIGURE 1 – Interval patterns in the Euclidean space.

Equivalence class, (frequent) closed interval pattern and generator. Two interval patterns c and d with same image are equivalent, i.e. $c^{\square} = d^{\square}$: we write $c \cong d$. $\cong$ is an *equivalence relation*, i.e. reflexive, transitive and symmetric. The set of patterns equivalent to a pattern d is denoted by $[d] = \{c | c \cong d\}$ and called the equivalence class of d. A pattern d is *closed*, and noted CIP, if there does not exist any pattern e such as $d \sqsubseteq e$ with $d \cong e$. Dually, a pattern d is a *generator*, and noted GIP, if there does not exist a pattern e such as $e \sqsubseteq d$ with $d \cong e$. Finally, a pattern d is *frequent* if its image has a higher cardinality than a given minimal support threshold $minSup$.

We illustrate these definitions with two dimensional interval patterns and their representation in Figure 1, considering attributes m_1 and m_3. $\langle [4,5],[6,8] \rangle \cong \langle [4,6],[6,8] \rangle$ with image $\{g_1, g_4\}$. $\langle [4,6],[6,8] \rangle$ is not closed as $\langle [4,6],[6,8] \rangle \sqsubseteq \langle [4,5],[6,8] \rangle$, and both patterns have same image, i.e. $\{g_1, g_4\}$. $\langle [4,5],[5,8] \rangle$ is closed. $\langle [4,6],[5,8] \rangle$ and $\langle [4,5],[4,8] \rangle$ are the generators of the closed interval pattern $d_1 = \langle [4,5],[5,8] \rangle$ with image $\{g_1, g_3, g_4, g_5\}$. Among the four patterns in Figure 1, d_1 is the only frequent interval pattern with $minSup = 3$.

Based on the above semantics, an equivalence class is a set of rectangles containing the same set of object descriptions, with a (unique) closed pattern corresponding to the smallest rectangle, and one or several generator(s) that are largest rectangle(s).

4.4 IS-itemsets versus interval patterns

Recall that interordinal scaling allows to build binary data encoding all interval of values from a numerical dataset. Therefore, one may attempt to mine classical closed itemsets and generators in these data with existing data-mining algorithms. Here we show why this should be avoided.

Local redundancy of IS-itemsets. Extracting all IS-itemsets in our example (from Table 2) gives $31,487$ IS-itemsets. This is surprising since there are 360 possible interval patterns. In fact, many IS-itemsets are locally redundant. For example, $\{m_1 \leq 5\}$ and $\{m_1 \leq 5, m_1 \leq 6\}$ both correspond to interval pattern $\langle [4,5],[7,9],[4,8] \rangle$: the constraint $m_1 \leq 6$ is redundant w.r.t. $m_1 \leq 5$ on the set of values W_{m_1}. Hence there is no 1-1-correspondence between IS-itemsets and interval patterns. However, there is a 1-1-correspondence between closed IS-itemsets and CIP only [4]. Later we show that local redundancy of IS-itemsets makes the computation of closed sets very hard.

Global redundancy of IS-itemset generators. Since IS-itemset generators are the smallest itemsets, they do not suffer of local redundancy. However, we remark another kind of redundancy, called global redundancy : it happens that two different and incomparable IS-itemset generators correspond to two different interval pattern generators, but one subsuming the other. In Table 2, both IS-itemsets $N_1 = \{m_1 \leq 4, m_3 \leq 5\}$ and $N_2 = \{m_1 \leq 4, m_3 \leq 6\}$, with same image $\{g_3\}$ are generators, i.e. there does not exist a subset of these itemsets with same image. However, their corresponding interval pattern are respectively $c = \langle [4,4], [7,9], [4,5] \rangle$ and $d = \langle [4,4], [7,9], [4,6] \rangle$ and we have $d \sqsubseteq c$, while $c^{\Box} = d^{\Box}$, hence c is not an interval pattern generator.

4.5 Algorithms

We detail a depth-first enumeration of interval patterns, starting with the most frequent one. Based on this enumeration, we design the algorithms *MinIntChange* and *MinIntChangeG* for extracting respectively frequent closed interval patterns (FCIP) and frequent interval pattern generators (FIPG).

Interval pattern enumeration. The basic idea of pattern generation lies in *minimal changes* for generating the direct subsumers of a given pattern. For example, two minimal changes can be applied to $[4,6]$. The first consists in replacing the right border with the value of W_{m_1} immediately lower that 6, i.e. 5, for generating the interval $[4,5]$. The second consists in repeating the same operation for the left border, generating the interval $[5,6]$. Repeating these two operations allows to enumerate all elements of $(D_{m_1}, \Box)$. A right minimal change is defined formally as, given $a, b, v \in W_m$, $a \neq b$, $mcr([a,b]) = [a,v]$ with $v < b$ and $\nexists w \in W_m$ s.t. $v < w < b$ while a left minimal change $mcl([a,b])$ is formally defined similarly. Minimal changes give direct next subsumers and implies a monotonicity property of frequency, i.e. support of $[a,v]$ is less than or equal to support of $[a,b]$. To avoid generating several times the same pattern, a lectic order on changes, or equivalently on patterns, is defined. After a right change, one can apply either a right or left change ; after a left change one can apply only a left change. Figure 2 shows the depth-first traversal (numbered arrows) of diagram of $(D_{m_1}, \Box)$. Backtrack occurs when an interval of the form $[w,w]$ is reached ($w \in W_{m_1}$), or no more change can be applied. Each minimal change can be interpreted in term of an IS-item. For example, if $[a,b]$ corresponds to the IS-itemsets $\{m \geq a, m \leq b\}$ then $mcr([a,b]) = [a,v]$ corresponds to $\{m \geq a, m \leq b, m \leq v\}$, i.e. adding $m \leq v$ to the original IS-itemset. The same applies dually to left minimal changes. These IS-items characterizing minimal changes are drawn on Figure 2. This figure accordingly represents a prefix-tree, factoring out the effort to process common prefixes or minimal changes, and avoiding redundancy problems inherent in interordinal scaling. The generalization to several attributes is straightforward. A lectic order is classically defined on numerical attributes as a lexicographic order, e.g. $m_1 < m_2 < m_3$. Then changes are applied as explained above for all attributes respecting this order, e.g. after applying



FIGURE 2 – Depth-first traversal of $(D_{m_1}, \Box)$.

a change to attribute m_2, one cannot apply a change to attribute m_1.

Extracting FCIP with MintIntChange. The pattern enumeration starts with the minimal pattern w.r.t $\sqsubseteq$ and generates its direct subsumers with lower or equal support. The next problem now is that minimal changes do not necessarily generate patterns with strictly smaller support. Therefore, we should apply changes until a pattern with different support is generated to identify a closed interval pattern (FCIP) but this would not be efficient. We adopt the idea of the algorithm *CloseByOne* [9] : before applying a minimal change, the closure operator $(.)^{\square\square}$ is applied to the current pattern, allowing to skip all equivalent patterns. Indeed, the minimal pattern d w.r.t. $\sqsubseteq$ is closed as it is given by $d = G^{\square}$. Applying a minimal change returns a pattern c with strictly smaller support, since $d \sqsubseteq c$ and d is closed. If c is frequent, we can continue, apply the closure operator and next changes in lectic order, allowing to completely enumerate all FCIP. Since a FCIP may have several different associated generators, it can be generated several times. Still following the idea of *CloseByOne*, a canonicity test can be defined according to lectic order minimal changes. Consider a pattern d generated by a change at attribute $m_j \in M$. Its closure is given by $d^{\square\square}$. If $d^{\square\square}$ differs from d for some attributes $m_h \in M$ such as $m_h < m_j$, then $d^{\square\square}$ has already been generated : it is not canonically generated, hence the algorithms backtracks.

Extracting FIPG with MintIntChangeG. We now adapt *MinIntChange* to extract FIPG, following a well-known principle in itemset-mining algorithms [10]. For any FCIP d, a minimal change implies that the support of the resulting pattern c is strictly smaller than the support of d. Therefore, c is a good generator candidate of the next FCIP. Accordingly, at each step of the depth-first enumeration a FGIP candidate c is generated from the previous one b, by applying a minimal change characterized by $b^{\square\square}$. Then, each candidate c has to be tested to be a true generator or not. We know that the candidate has no subsumers in its branch with same support. However, it could exist a branch with another FGIP e with same image and resulting from less changes. Considering the lectic order on minimal changes, we use a reverse traversal of the tree (see Figure 2 : 7,8,9,10,1,4,5,2,3,6), as already suggested in the binary case in [10]. Since generators correspond to largest rectangles, i.e. on which the fewest minimal changes have been applied, if c is not a generator, a generator e associated to its equivalence class has already been generated, and c is discarded. To check the existence of e, we look up in an auxiliary data-structure storing already extracted FGIP. Precisely, if the data structure contains a FGIP e with same support than candidate c, such that $e \sqsubseteq c$, c is discarded, and the algorithm backtracks. Otherwise c is declared as a FIPG and stored. We have experimented the *MinIntChangeG* algorithm with two well-known and adapted data structures, a trie and a hashtable.

5 Experiments

We evaluate the performances of the algorithms designed in Java : *MinIntChange*, *MinIntChangeG-h* with auxiliary hashtable and *MinIntChangeG-t* with auxiliary trie. Recalling that closed IS-itemsets and CIP are in 1-1-correspondence, we compare the performance for mining interordinal scaled data with the closed-itemset-mining algo-

rithm *LCMv2* [1]. For studying the global redundancy effect of IS-itemset generators, we use the generator-mining-algorithm *GrGrowth* [2]. Both implementations in C++ are available from the authors. All experiments are conducted on a 2.50Ghz machine with 16GB RAM running under Linux 2.6.18-92.e15. We choose dataset from the Bilkent repository [3], namely Bolts (BL), Basketball (BK) and Airport (AP), AP being worst case where each attribute value is different.

First experiments compare *MinIntChange* for extracting FCIP and *LCMv2* for extracting equivalent frequent closed IS-itemsets in Table 3. Second experiments consist in extracting frequent interval pattern generators (FIPG) with algorithms *MinIntChange-h* and *MinIntChange-t*. We also extract frequent itemset generators (FISG) in corresponding binary data after interordinal scaling with *GrGrowth* for studying the global redundancy effect in Table 3.

Dataset	minSupp	MinIntChange	LCMv2	$\|FCIP\|$
BL	80%	< 50	< 50	1,130
	50%	252	**100**	32,107
	25%	1,215	**1,060**	171,192
	10%	**1,821**	1,950	268975
	1	**1,905**	2,090	272,223
AP	80%	4,595	**1,470**	346,741
	50%	**143,939**	149,580	16,214,345
	25%	**413,805**	899,180	58,373,631
	10%	**506,985**	6,810,125	80,504,566
	1	**517,548**	6,813,591	82,467,124

FIGURE 3 – Execution time for extracting FCIP

In both cases, using binary data is better when the minimal support is high (e.g. 90%). For low supports, a critical issue, our algorithms deliver better execution times. Most importantly, the global redundancy effect discards the use of binary data, e.g. only 1.6% of all FISG are actually FIPG in dataset BL. Finally, the algorithm *MinIntChangeG-t* outperforms *MinIntchangeG-h*. *MinIntChangeG-t* however needs more memory : it stores each closed set of objects as a word in the trie with associated associated FIPGs.

It is very interesting to analyse the compression ability of closed interval patterns and generators. For that, we compare in each dataset the number of those patterns w.r.t. to all possible interval patterns. It gives the ratio of closed (generators) in the whole search space. In both cases, ratio varies between 10^{-7} and 10^{-9}. This means that the volume of useful interval patterns, either closed or generators, is very low w.r.t. the set of all possible interval patterns, justifying our interest in equivalence classes.

1. http://research.nii.ac.jp/~uno/codes.htm
2. http://www.comp.nus.edu.sg/~wongls/projects/pattern-spaces/grgrowth-v1/
3. http://funapp.cs.bilkent.edu.tr/

Dataset	minSupp	GrGrowth	MinIntChangeG-h	MinIntChangeG-t	$\|FIPG\|$	$\|FISG\|$	$\frac{\|FIPG\|}{\|FISG\|}$
BL	90%	< 50	< 50	< 50	176	194	90%
	80%	< 50	< 50	< 50	1,952	2,823	69%
	50%	**150**	1,212	529	66,350	222,088	29%
	25%	**3,432**	27,988	3,893	411,442	3,559,419	11%
	1	123,564	438,214	**24,141**	1,165,824	69,646,301	**1.6%**
BK	90%	< 50	1,268	1,207	67,737	75,058	84%
	85%	**4,565**	26,154	12,139	554,956	799,574	69%
	80%	Untractable	512,126	**107,700**	2,730,812	NA	NA

TABLE 3 – Execution time for extracting FIPG and global redundancy evaluation.

6 Concluding remarks

We discussed the important problem of pattern discovery in numerical data with an original formalization of interval patterns. The classical FCA/itemset-mining settings are adapted accordingly : from a closure operator naturally rise the notions of equivalence classes, closed and generator patterns, and we designed corresponding algorithms. An appropriate semantics of interval patterns shows from a theoretical (redundancy) and practical (computation times) points of view that mining equivalent binary data (encoding all possible intervals) is not acceptable. This is due to the fact the interval patterns are provided with a stronger partial ordering than IS-itemsets (classical set inclusion), hence pattern structures yield significantly less generators w.r.t. their semantics.

In data-mining, closed patterns and their generators are crucial for extracting valid and informative association rules [3], while generators can be preferable to closed patterns following the minimum descriptions length principle. How these notions can be shifted to interval patterns is an original perspective of research rising questions concerning missing values, fault-tolerant patterns, and interestingness measures that are critical issues even in classical itemset mining : although the compression ability of closed interval patterns and generators is spectacular, the number of patterns remains too high for large datasets. However, bringing the problem of numerical pattern mining into well known settings may enable these perspectives of research.

References

[1] B. Ganter and R. Wille. *Formal Concept Analysis*. Springer, 1999.

[2] B. Ganter and S. O. Kuznetsov. Pattern structures and their projections. In *9th Int. Conf. on Conceptual Structures*, LNCS (2120), pages 129–142. Springer, 2001.

[3] Y. Bastide, R. Taouil, N. Pasquier, G. Stumme, and L. Lakhal. Mining frequent patterns with counting inference. *SIGKDD Expl.*, 2(2) :66–75, 2000.

[4] M. Kaytoue, S. O. Kuznetsov, A. Napoli, and S. Duplessis. Mining gene expression data with pattern structures in formal concept analysis. *Inf. Sci.*, 181(10) :1989–2001, 2011.

[5] R. Srikant and R. Agrawal. Mining quantitative association rules in large relational tables. In *ACM SIGMOD Int. Conf. on Management of Data*. ACM, 1996.

[6] M. Kaytoue, S. O. Kuznetsov, and A. Napoli. Pattern Mining in Numerical Data : Extracting Closed Patterns and their Generators. Research Report RR-7416, INRIA, 2010.

[7] M. Kaytoue, S. O. Kuznetsov, and A. Napoli. On pattern discovery in numerical data with formal concept analysis. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2011. To appear.

[8] G. Stumme, R. Taouil, Y. Bastide, N. Pasquier, and L. Lakhal. Computing iceberg concept lattices with titanic. *Data Knowl. Eng.*, 42(2), 2002.

[9] S. O. Kuznetsov and S. A. Obiedkov. Comparing performance of algorithms for generating concept lattices. *J. Exp. Theor. Artif. Intell.*, 14(2-3) :189–216, 2002.

[10] T. Calders and B. Goethals. Depth-first non-derivable itemset mining. In *SIAM International Conference on Data Mining*, 2005.